


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : A61B 17/70</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/57801</p> <p>(43) International Publication Date: 5 October 2000 (05.10.00)</p>
<p>(21) International Application Number: PCT/US00/08318</p> <p>(22) International Filing Date: 29 March 2000 (29.03.00)</p> <p>(30) Priority Data: 60/126,997 30 March 1999 (30.03.99) US</p> <p>(71) Applicant: SURGICAL DYNAMICS, INC. [US/US]; 150 Glover Avenue, Norwalk, CT 06856 (US).</p> <p>(72) Inventors: NICHOLS, David; 40 Salem Road, Trumbull, CT 06611 (US). FINLEY, Eric; 8606 Hebrides, San Diego, CA 92126 (US).</p> <p>(74) Agent: GERSHON, Neil, D.; U.S. Surgical, 150 Glover Avenue, Norwalk, CT 06856 (US).</p>		<p>(81) Designated States: AU, CA, JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: APPARATUS FOR SPINAL STABILIZATION



(57) Abstract

An apparatus is disclosed for connecting first and second elongated spaced apart spinal rods to one another which includes an elongated body portion, a clamp portion depending from the body portion for engaging a spinal rod, the clamp portion defining a deformable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body, and structure operatively associated with the clamp body which is configured to effectuate movement of the opposed clamp arms of the clamp body between the first and second positions.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

APPARATUS FOR SPINAL STABILIZATION

5 CROSS-REFERENCE TO RELATED APPLICATIONS

The subject application claims priority to U.S. Provisional Patent Application No. 60/126,997 filed March 30, 1999, the disclosure of which is herein incorporated by reference in its entirety.

BACKGROUND OF THE DISCLOSURE

10 1. Field of the Disclosure

The subject disclosure relates to implantable spinal stabilization systems for surgical treatment of spinal disorders, and more particularly, to an apparatus for connecting cylindrical spinal rods of a spinal stabilization system to one another across the spinous process.

15 2. Background of the Related Art

The spinal column is a complex system of bones and connective tissue which protects critical elements of the nervous system. Despite these complexities, the spine is a highly flexible structure, capable of a high degree of curvature and twist through a wide range of motion. Trauma or developmental irregularities can result in spinal pathologies which limit this range of motion.

For many years, orthopedic surgeons have attempted to correct spinal irregularities and restore stability to traumatized areas of the spine through immobilization. Over the past ten years, spinal implant systems have been developed to achieve immobilization. Examples of such systems are disclosed in U.S. Patent Nos. 5,102,412 and 5,181,917. Such systems often include spinal instrumentation having connective structures such as elongated rods which are placed on opposite sides of the portion of the

spinal column intended to be immobilized. Screws and hooks are commonly utilized to facilitate segmental attachment of such connective structures to the posterior surfaces of the spinal laminae, through the pedicles, and into the vertebral bodies. These components provide the necessary stability both in tension and compression to achieve immobilization.

5 It has been found that when a pair of spinal rods are fastened in parallel on either side of the spinous process, the assembly can be significantly strengthened by using at least one additional rod to horizontally bridge the pair of spinal rods. An example of a cross brace assembly of this type is disclosed in U.S. Patent No. 5,084,049. Devices such as these commonly consist of a threaded rod for providing the desired lateral support. The
10 threaded rod is fastened to each of the spinal rods by clamps located on each end thereof. However, this configuration is bulky and can cause irritation of the patient's back muscles and other tissue which might rub against the device. A cross brace assembly that overcomes the problems associated with bulky stabilization assemblies by fitting closer to the spine, preferably in the same general plane as the cylindrical spinal rods, is disclosed in
15 commonly assigned U.S. Patent No. 5,989,251.

It has also been found that the distance between a pair of spinal rod located on either side of the spine can vary depending upon the anatomy of the patient and the manner in which the rods are secured to the spinous process. Thus, transverse rod connectors have been designed with adjustable bridging structures to accommodate this
20 variability, as disclosed, for example, in U.S. Pat. Nos. 5,752,955 and 5,947,966.

Most existing transverse connectors consist of rods, plates, and bars linked to the longitudinal rods by coupling mechanisms with set screws, nuts, or a combination of each. These connectors require several components and instruments to build the constructs. Each additional component or instrument required to assemble the connectors
25 adds to the complexity of the surgical procedure. Examples of connectors constructed

from multiple components are disclosed in U.S. Patent Nos. 5,312,405, 5,334,203 and 5,498,263.

It would be beneficial to provide an improved device to transversely connect spinal rods of a spinal stabilization system to one another which utilizes a minimum number of components parts and surgical instrumentation, and which has a low-profile so as to fit closely to the spine, and which may be easily adjusted during a spinal stabilization procedure.

SUMMARY OF THE DISCLOSURE

The subject disclosure is directed to an apparatus for connecting two conventional spinal rods of a spinal stabilization system to one another in such a manner so as to provide an adjustable low-profile rigid linkage therebetween. In accordance with a preferred embodiment of the subject disclosure, the apparatus includes an elongated body portion and a clamp portion depending from the body portion for engaging a spinal rod.

Preferably, the clamp portion defines a deflectable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body. In addition, structural means are operatively associated with the clamp body to effectuate the movement of the opposed clamp arms of the clamp body between the first and second positions.

In accordance with one aspect of the disclosure, the structural means for moving the opposed clamp arms between the first and second positions comprises a cam lug configured for reception within a bore formed in the clamp body and adapted for axial rotation within the bore. The cam lug has a generally cylindrical body with camming

surfaces formed thereon, and the reception bore is defined at least in part by interior walls. In operation, the camming surfaces of the cam lug are adapted and configured for bearing against the interior walls of the reception bore upon rotation of the cam lug within the reception bore.

5 In accordance with another aspect of the subject disclosure, the structural means for moving the opposed clamp arms between the first and second positions comprises an engagement tab projecting outwardly from an exterior surface of the clamp body, and a recess formed within the clamp body spaced from the engagement tab. In operation, the engagement tab is grasped with a tool and pulled outwardly to enlarge a gap
10 between the opposed clamp arms.

 In accordance with one aspect of the subject disclosure the elongated body portion has a predetermined span length for extending between a pair of elongated spinal rods disposed in parallel relationship. Alternatively, the elongated body portion has a span length that is selectively variable for extending between a pair of elongated spinal rods
15 disposed in parallel relationship. Accordingly, the elongated body portion includes means for selectively adjusting the length of the body portion.

 In accordance with one aspect of the subject disclosure, the means for selectively adjusting the length of the body portion includes a first body portion having an axial bore defined therein and a second body portion having an axial shaft for reception
20 within the axial bore of the first body portion, and a locking ring for radially compressing the first body portion against the second body portion when the axial shaft is disposed within the axial bore. In accordance with another aspect of the subject disclosure, the means for selectively adjusting the length of the body portion includes a first body portion having a threaded bore defined therein and a second body portion having an threaded shaft
25 for reception within the threaded bore of the first body portion.

These and other unique features of the apparatus disclosed herein and the method of installing the same will become more readily apparent from the following description of the drawings.

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

So that those having ordinary skill in the art to which the disclosed apparatus appertains will more readily understand how to construct and use the same, reference may be had to the drawings wherein:

Fig. 1 is a perspective view of a spinal stabilization system for
10 immobilizing a region of the spinal column which includes variable and fixed length rod connecting apparatus constructed in accordance with preferred embodiments of the subject disclosure, and a set of bone screws with linear locking mechanisms;

Fig. 1A a perspective view of another spinal stabilization system for
immobilizing a region of the spinal column which includes a set of bone screws with top-
15 loading rotatable locking mechanisms;

Fig. 2 is a top plan view of the spinal stabilization system of Fig. 1
implanted on the posterior side of the spinal column;

Fig. 3 is a perspective view of the variable length rod connecting apparatus
of the subject disclosure with the parts thereof separated for ease of illustration;

20 Fig. 4 is a perspective view of the fixed length rod connecting apparatus of
the subject disclosure;

Fig. 5 is a cross-sectional view taken along line 5-5 of Fig. 1 illustrating the
clamping portion of the rod connecting apparatus of Fig. 3 in fastened condition;

Fig. 6 is a perspective view of the cam lug of the subject disclosure which facilitates movement of the clamping portion of the rod connecting apparatus of Figs. 3 and 4 between first and second positions;

Fig. 7 is a top plan view of the cam lug illustrated in Fig. 6 showing the
5 opposed lateral cam surfaces thereof;

Fig. 8 is a perspective view of the variable length rod connecting apparatus of Fig. 3 prior to installation between a pair of parallel spinal rod;

Fig. 9 is a perspective view of the variable length rod connective apparatus shown in Fig. 8, with the clamping portions thereof engaged to the spinal rods in a
10 frictionally engaged condition;

Fig. 10 corresponds to the operative step shown in Fig. 9 and illustrates the relative movement of the arms of the clamping portion between an initial position and a frictionally engaged position with respect to a spinal rod extending therethrough prior to being moved into a tightly secured position about the periphery of the spinal rod;

Fig. 11 is a perspective view of the variable length rod connecting apparatus
15 shown in Figs. 7 and 8, with the locking collet moved into a locked position to maintain the length of the connector using a surgical instrument;

Fig. 12 is a perspective view of the variable length rod connecting apparatus shown in Fig. 7 and 8, illustrating the positioning of the cam lugs into the reception areas
20 of the clamping portions;

Fig. 13 is a perspective view of the variable length rod connecting apparatus shown in Fig. 12, illustrating the rotation of the cam lugs to facilitate movement of the clamping portions into a securely fastened position to fixedly connect the apparatus to the spinal rods;

Fig. 14 is a perspective view of another variable length rod connecting apparatus constructed in accordance with a preferred embodiment of the subject disclosure with the parts thereof separated for ease of illustration;

5 Fig. 15 is a perspective view of still another variable length rod connecting apparatus constructed in accordance with a preferred embodiment of the subject disclosure with the parts thereof separated for ease of illustration; and

Fig. 16 is a perspective view of a kit containing various components and tools constructed in accordance with the subject disclosure.

10 These and other features of the apparatus disclosed herein will become more readily apparent to those having ordinary skill in the art from the following detailed description of the invention taken in conjunction with the drawings.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 Referring now to the drawings wherein like reference numerals identify similar structural elements of the subject apparatus, there is illustrated in Figs. 1 and 2 a spinal stabilization system constructed in accordance with a preferred embodiment of the subject disclosure and designated generally by reference numeral 10.

20 Referring to Fig. 1, spinal stabilization system 10 includes a pair of elongated spinal rods 12 and 14. The spinal rods are adapted for parallel deployment on either side of the spinous process, as illustrated in Fig. 2. Spinal rods 12 and 14 are of a conventional type, constructed from a bio-compatible material and having a circular cross-section with a smooth outer surface finish. Spinal rods 12 and 14 are segmentally secured to the bones of the spinous process by a variety of structural components including, for example, bone screws 18.

Bone screws 18 have linear locking mechanisms of the type disclosed in commonly assigned U.S. Patent No. 5,989,251, the disclosure of which is herein incorporated by reference in its entirety. An alternative spinal stabilization system designated generally by reference numeral 10a is illustrated in Fig. 1A. Spinal

5 stabilization system 10a includes bone screws 18a that have top-loading rotatable locking mechanisms of the type disclosed in commonly assigned U.S. Appln. Serial No. 09/487,942, the disclosure of which is herein incorporated by reference in its entirety.

It has been found that when a pair of spinal rods are fastened to one another in parallel relationship on either side of the spinous process, as illustrated in Figs. 1 and 2, 10 the stabilization system can be significantly strengthened. Thus, the spinal rods 12 and 14 of stabilization system 10 are connected to one another by a plurality of rod linking devices constructed in accordance with a preferred embodiment of the subject disclosure. Figs. 1 and 2 illustrate two embodiments of the rod linking device of the subject disclosure constructed from high- strength, low-weight, corrosion resistant, bio-compatible metal 15 alloy, such as, for example, titanium or stainless steel.

The first embodiment is a variable length rod linking device designated generally by reference numeral 20. (See Fig. 3). The second embodiment has a fixed length and is designated by reference numeral 60. (See Fig. 4). Rod linking device 20 is adapted and configured to be selectively adjusted during a spinal stabilization procedure to 20 bridge the gap that exists between spinal rod 12 and 14. In contrast, rod linking device 60 has a predetermined span length and is configured to bridge a fixed gap between spinal rods 12 and 14. As discussed in greater detail hereinbelow, rod linking devices 20 and 60, also referred to herein as transverse rod connectors 20 and 60, both have a unique rod engaging system in the form of a generally u-shaped deflectable clamping portion or hook.

Referring now to Fig. 3, there is illustrated the variable length rod linking device 20 of the subject disclosure. Rod connector 20 includes first and second body portions 22 and 24. The distal section 22d of the first body portion 22 has a slight outward taper so that the outer diameter of the distal section 22d is slightly greater than that of the main section of the first body portion 22. In addition, an axial reception bore 26 is defined in the first body portion 22 for receiving the second body portion 24. An annular locking collet 28 is operatively associated with the first body portion 22 for securely retaining the second body portion 24 within the axial reception bore 26. More particularly, the distal section 22d of the first body portion 22 has a pair of diametrically opposed compression slots 30a and 30b defined therein, which extend from the free distal end of body portion 22 to a location intermediate its length, to facilitate radial compression of the distal end section 22d of body portion 22 against the second body portion 24 when it is disposed within axial bore 26.

Annular locking collet 28 is coaxially positioned on body portion 22 and is configured for axial movement along the length thereof, between an annular blocking flange 34 disposed intermediate the length of body portion 22 and a pair of diametrically opposed blocking ribs 36a and 36b disposed at the free distal end of body portion 22. In use, movement of the locking collet 28 between an initial position adjacent annular blocking flange 34 and a final position adjacent blocking ribs 36a and 36b causes radial compression of the distal end section 22d of body portion 22, as the locking collet 28 moves relative to the outwardly tapered distal section 22d of body portion 22.

As best seen in Fig. 3, blocking ribs 36a and 36b are dimensioned and configured to facilitate the mounting of locking collet 28 on body portion 22 during assembly of the connector 20. More specifically, during assembly, locking collet 28 is slid over blocking ribs 36a and 36b for positioning within the area defined between the

blocking ribs and annular blocking flange 34. Manipulation of locking collet 28 is aided by the provision of tab 28a. Also shown in Fig. 3 is a location guide hole 38 disposed between the free distal end of body portion 22 and the annular blocking flange 34. The hole 38 enables a surgeon to locate the position of the collet 28 during locking to ensure
5 collet 28 is moved sufficiently axially to the final locking position.

 The second body portion 24 of rod connector 20 is defined by an axial shaft having a uniform outer diameter along substantially the entire length thereof. The outer diameter of the axial shaft is about approximately equal to the inner diameter of the axial bore 26 defined within the first body portion 22, so that an interference fit exists
10 therebetween when the two components are telescopically connected to one another during assembly. A retaining ring 24a is provided to retain first and second body portions 24 and 22 together, when assembled, as a lip (not shown) on first body portion 22 engages the larger diameter retaining ring 24a.

 With continuing reference to Fig 3 in conjunction with Figs. 5 through 7,
15 rod connector 20 includes a unique rod engaging system for securely fastening the transverse connector to spinal rods 12 and 14 during a spinal stabilization procedure with imparting undue stress upon the spine. This system consists of deflectable rod clamps 42 and 44 which depends from the first and second body portion 22 and 24, respectively, for securely engaging spinal rods 12 and 14, respectively. Rod clamp 42 depending from body
20 portion 22 includes a first and second clamp arms 42a and 42b between which is defined a gap or channel 43a for accommodating spinal rod 12. Similarly, rod clamp 44 which depends from body portion 24 includes first and second opposed clamp arms 44a and 44b between which is defined a gap or channel 43b. Each rod clamp 42, 44 has a respective reception port 46, 48 for receiving a camming lug 50. The camming lug 50 is configured
25 to effectuate movement of a clamp 42, 44 from an initial position wherein the clamp is

frictionally engaged with a spinal rod to a final position wherein the clamp is tightly compressed about the periphery of the spinal rod, as shown in Fig. 5.

Referring to Figs 6 and 7, camming lug 50 includes a main body portion 52, illustratively generally elliptical in cross section, with enlarged radially outwardly projecting curved lateral camming surfaces 52a and 52b for interacting with the interior walls of reception ports 46, 48. Camming lug 50 further includes a central aperture 54 for receiving an appropriate tool or implement designed to facilitate axial rotation of camming lug 50 within reception ports 46, 48 during a spinal stabilization procedure (see Fig. 13). Advantageously, the rotational forces imparted upon camming lug 50 during assembly do not impose undue stress on the patient's spine during a stabilization procedure. A retention flange 56 is provided at the lower end of the main body portion 52 of camming lug 50 for cooperating with retention channels 46a, 48a formed in reception portions 46, 48, respectively. This interaction is intended to inhibit the displacement of the camming lugs from the reception ports during shipment, as well as during a surgical procedure.

In use, rotation of the camming lug 50 within reception ports 46, 48 causes the lateral camming surfaces 52a, 52b to bear against the walls of reception ports 46, 48, urging the walls to expand radially outwardly. In what can best be described as a scissors-like action, the outward expansion of the port walls causes the clamp arms 42a, 42b and 44a, 44b to move inwardly toward one another so as to reduce the size or diameter of the gaps or channels 43a, 43b defined therebetween, respectively. As a result, spinal rods 12 and 14 are compressed tightly between clamp arms 42a, 42b and 44a, 44b, as illustrated, for example, in Fig. 5. It should be recognized that the amount of outward deflection of the walls of the reception bore caused by rotating the camming lugs, and the resultant inward compression of the clamp arms is relatively small, as the arms must only move a

sufficient distance so as to clamp about the spinal rod after having already achieved a frictional engagement therewith upon initial assembly.

Referring now to Figs. 8 through 13, there is illustrated, in sequential order, one embodiment of the operative steps associated with mounting the rod linking device 20 of the subject disclosure to a pair of parallel spinal rods 12 and 14 during a spinal stabilization procedure. As illustrated in Fig. 8, initially the rod linking device 20 is moved into approximation with spinal rods 12 and 14 with the body portions 22 and 24 telescopically mated to one another, i.e., body portion 24 is disposed within the axial reception bore 26 of body portion 22. At such a time, locking collet 28 is positioned intermediate the distal end section 22 of body portion 22, proximal of compression slots 30a and 30b, and the outwardly tapered portion of the distal section 22d

Then, as illustrated in Fig. 9, the rod clamps 42, 44 are brought into engagement with spinal rods 12 and 14, respectively. At such a time, the rod clamps are not securely fastened to the spinal rods and may moved along the length of the spinal rods or be removed from the rods by the surgeon for repositioning if such action becomes necessary. Fig. 10 illustrates the engagement of a rod clamp with a spinal rod, whereby the “broken lines” illustrate the clamp in a non-engaged position and the “solid lines” illustrate the rod clamp in a frictionally engaged position.

Referring to Fig. 11, after rod clamps 42 and 44 are engaged to spinal rod 12 and 14, respectively, the length of rod linking device 20 is set. This is accomplished by moving locking collet 28 from its initial location adjacent blocking flange 34 toward the blocking ribs 36a and 36b. This movement is accomplished by an appropriate tool, such as surgical pliers 70 or a similar surgical instrument. As the collect 28 translates in the direction of arrow “A”, it moves against the tapered surfaces of the distal end section 22d of body portion 22, causing the distal end section 22d of body portion 22 to radially

compress against the cylindrical outer surface of body portion 24 disposed within axial bore 26. When locking collet 28 is moved past location guide hole 38, the user is informed that it is in the locked position.

Referring to Fig. 12, once the appropriate span length of rod linking device 20 has been set, camming lugs 50 are inserted into the reception ports 46 and 48 of deflectable rod clamp 42 and 44. At such a time, the camming surfaces 50a and 50b of the camming lugs are not bearing against the walls of the reception ports within which they are disposed. Consequently, the position of the rod clamps can still be adjusted if such action is necessary. It is contemplated in a preferred embodiment that the system is shipped and utilized with the camming lugs 50 already in reception ports 46 and 48. Thus, in this embodiment, in the steps shown in Figs. 8, 9 and 11 the camming lugs would already be in place, saving the surgeon the additional step of inserting the individual camming lugs 50 in reception ports 46, 48.

Alternatively, it is envisioned that the rod linking devices of the subject disclosure could be shipped with the camming lugs 50 already positioned within the reception ports 46, 48 so as to reduce the number of steps required to secure the spinal rods 12, 14 to one another during a spinal stabilization procedure. Thus, the operative step illustrated in Fig. 12 would become unnecessary.

In either instance, to securely fasten the rod clamps 42, 44 to spinal rods 12, 14, camming lugs 50 are axially rotated in a clock-wise direction within reception ports 46, 48 using an appropriate surgical tool or implement, such as for example, lug driver 75. This axial rotation causes the outwardly projecting camming surfaces 52a, 52b to bear against the interior walls of the reception ports 46, 48, urging them to move radially outwardly. As a result, an equal and opposite scissors-like movement of the opposed clamp arms occurs, causing the opposed clamp arms of each rod clamp 42, 44 to tightly engage

the outer periphery of the spinal rods 12, 14, as best seen, for example, in Fig. 5, without imparting undue stress on the spine. Once tightly engaged about the spinal rods, the rod clamps 42, 44 are essentially immobilized.

While the operative steps involved in mounting and securing rod linking device 20 to a pair of spinal rods has been described with respect to a sequential order, it will be readily apparent to those having ordinary skill in the art to which the subject disclosure appertains that the order or sequence of the operative steps can be altered or modified. For example, in an alternative and preferred embodiment, the rod clamps can be secured to the spinal rods prior to setting the desired length of the linking device. In this preferred version, the camming lugs 50 are rotated to the clamps 42 and 44 on the spinal rods and then the locking collet 28 is moved axially to its final locking position.

Referring to Fig. 4, the rod linking device 60 of the subject disclosure has a predetermined span length configured to extend a fixed distance across the spinous process between a pair of parallel spinal rods 12 and 14, as illustrated in Figs. 1 and 2. Rod linking device 60 includes a main body portion 62 defining a longitudinal axis. Body portion 62 has a low profile construction for fitting closely to the spine, so as to reduce any bulkiness associated with spinal stabilization system 10. Deflectable rod clamps 72 and 74 depend from the opposed ends of the main body portion 62 for securely engaging spinal rods 12 and 14, respectively. Rod clamps 72, 74 are substantially identical to rod clamps 42, 44 of rod connector 20 and include reception ports 76, 78, respectively for receiving camming lugs 50. As in the previous embodiment, camming lugs 50 are configured to effectuate movement of the opposed clamp arms of rod clamps 72, 74 from an initial position in frictional engagement with the spinal rods to a final position tightly secured about the periphery of the spinal rods.

Rod linking device 60 is preferably provided in several different span lengths ranging from about 16mm in length to about 24mm in length, in about 2 mm increments. Additional lengths with varying increments are also contemplated. Referring to Fig. 16, in accordance with the subject disclosure a kit 100 is provided defined by a
5 packing enclosure 110 containing, among other things, a plurality of rod linking devices 60a-60c, each of which has a different preset span length for bridging the gap between a pair of elongated spinal rods. For example, the kit 100 could include a rod connector 60a having a span length of about 16mm, a rod connector 60b having a span length of about 18mm, and a rod connector 60c having a span length of about 20mm.

10 Preferably, the rod connectors 60a-60c would be packaged with camming lugs 50 already installed in the reception ports of the of clamps of each connector. Alternatively, a plurality of camming lugs 50 could be provided in the package separate from the connectors. The kit would also include an lug driver 75 for securing the camming lugs 50 within the reception ports of the linking devices. It is envisioned that kit 100 could also
15 contain a plurality of variable length rod linking devices 20a-20c and an appropriate surgical instrument 70 for moving the locking collet 28 along the length of the body portion, as described hereinabove with respect to Fig. 11.

Referring to Fig. 14, there is illustrated another rod linking device constructed in accordance with a preferred embodiment of the subject disclosure
20 designated generally by reference number 80. Rod linking device 80 is a variable length connector that includes first and second telescopically associated body portions 82 and 84 that are substantially similar to the first and second body portion 22 and 24 of rod linking device 20, which is described hereinabove and illustrated in Fig. 3. The first and second body portions 82, 84 of rod linking device 80 differ from those of rod linking device 20 in
25 that the rod clamps 92, 94 thereof do not employ camming lugs 50 to effectuate movement

of the opposed clamp arms 92a, 92b and 94a, 94b into a tightly engaged position about the periphery of the spinal rods. Instead, the gaps 93a, 93b defined between the opposed arms of each rod clamp 92, 94 are dimensioned and configured to tightly engage the periphery of the spinal rods without using a camming lug.

5 To engage a rod clamp 92, 94 to a spinal rod, the gap 93a, 93b between the opposed clamp arms thereof is radially expanded to allow the rod to enter the gap. This is accomplished by gripping a tab 96, 98 projecting outwardly from the leading edge of each rod clamp 92, 94 with an appropriate surgical instrument or tool (not shown), and drawing the outer clamp arm 92a, 94a away from the inner clamp arm 92b, 94b. The deflection of
10 the rod clamp 92, 94 and resultant radial expansion of the gap 93a, 93b is aided by the provision of cross-slots 95, 97 formed in rod clamps 92, 94 which provide areas within which the upper portion of the outer clamp arms 92a, 94a can effectively translate during the radial expansion of the gaps 93a, 93b. Once a spinal rod is situated within the gap 93a, 93b, the tab 96, 98 is released by the surgeon, allowing the outer clamp arm 92a, 94a to
15 return to its normal position. Thereupon, the inner diameter of the gap 93a, 93b is substantially equal to the outer diameter of the spinal rod and the rod connector 80 is essentially immobilized.

Referring to Fig. 15, there is illustrated yet another rod linking device constructed in accordance with a preferred embodiment of the subject disclosure
20 designated generally by reference number 120. Rod linking device 120 is also a variable length rod connector in that the span length thereof may be selectively and easily adjusted by a surgeon during a spinal stabilization procedure to accommodate different anatomical conditions. Rod linking device 120 includes a first body portion 122 which has an internally threaded axial bore 126 extending therethrough for receiving a corresponding
25 threaded shaft which defines the second body portion 124. During assembly, the second

body portion 124 is threadably secured within the internal bore 126 of the first body portion 122 to set the desired span length of rod linking device 120.

5 The body portions 122 and 124 of rod linking device 120 include deflectable rod clamps 142 and 144, respectively for securing engaging spinal rods rod during a surgical procedure. In contrast to the rod clamps of rod connectors 20, 60 and 80, described hereinabove, rod clamps 142, 144 do not include additional structures to facilitate movement of the opposed clamp arms 142a, 142b and 144a, 144b into a securely engaged position. Instead, the opposed clamp arms of rod clamps 142, 144 are simply snap-fit onto the spinal rods during a surgical procedure, so that the opposed clamp arms of
10 the rod clamps are tightly engaged about the periphery of the spinal rods.

Although the apparatus disclosed herein has been described with respect to preferred embodiments, it is apparent that modifications and changes can be made thereto without departing from the spirit and scope of the invention as defined by the claims. For example, while each embodiment of the subject rod linking device has been described in
15 conjunction with a particular type of deflectable rod clamping mechanism, it is envisioned and well within the scope of the subject disclosure that the various rod clamping mechanisms disclosed herein are easily interchangeable with respect to one another.

What is claimed is:

1. An apparatus for connecting spinal rods comprising:
 - a) an elongated body portion; and
 - b) a clamp portion depending from the body portion for
- 5 engaging a spinal rod, the clamp portion defining a deflectable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body.
- 10 2. An apparatus as recited in Claim 1, further comprising means operatively associated with the clamp body and configured to effectuate the movement of the opposed clamp arms of the clamp body between the first and second positions.
- 15 3. An apparatus as recited in Claim 2, wherein the means for moving the opposed clamp arms between the first position and the second positions comprises a cam lug configured for reception within a bore formed in the clamp body and adapted for axial rotation within the bore.
- 20 4. An apparatus as recited in Claim 3, wherein the cam lug has a body of generally elliptical cross section and has camming surfaces formed thereon, and the reception bore is defined at least in part by interior walls, whereby the camming surfaces of the cam lug are adapted and configured for bearing against the interior walls of the reception bore upon rotation of the cam lug within the reception bore.

5. An apparatus as recited in Claim 2, wherein the means for moving the opposed clamp arms between the first position and the second portion comprises an engagement tab projecting outwardly from an exterior surface of the clamp body, and a recess formed within the clamp body spaced from the engagement tab.

5

6. An apparatus as recited in Claim 1, wherein the elongated body portion includes opposed first and second end sections, and wherein a clamp portion depends from each end section of the elongated body portion.

10

7. An apparatus as recited in Claim 1, wherein the elongated body portion has a predetermined span length for extending between a pair of elongated spinal rods disposed in parallel relationship.

15

8. An apparatus as recited in Claim 1, wherein the elongated body portion has a span length that is selectively variable for extending between a pair of elongated spinal rods disposed in parallel relationship.

20

9. An apparatus as recited in Claim 8, wherein the elongated body portion include means for selectively adjusting the length of the body portion.

10. An apparatus as recited in Claim 9, wherein the means for selectively adjusting the length of the body portion includes a first body portion having an axial bore defined therein and a second body portion having an axial shaft for reception within the axial bore of the first body portion, and a locking ring for radially compressing the first body portion against the second body portion when the axial shaft is disposed within the axial bore.

11. An apparatus as recited in Claim 9, wherein the means for selectively adjusting the length of the body portion includes a first body portion having a threaded bore defined therein and a second body portion having an threaded shaft for reception within the threaded bore of the first body portion.

12. An apparatus for connecting spinal rod comprising:

- a) an elongated body portion;
- b) a clamp portion depending from the body portion for engaging a spinal rod, the clamp portion defining a deflectable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body;
- c) a cam lug configured for reception within a bore defined in the clamp body and adapted to effectuate movement of the opposed clamp arms of the clamp body between the first and second positions upon axial rotation within the bore.

13. An apparatus as recited in Claim 12, wherein the elongated body portion has a predetermined length for extending between a pair of elongated spinal rods disposed in parallel relationship.

5 14. An apparatus as recited in Claim 12, wherein the elongated body portion has a length that is selectively variable for extending between a pair of elongated spinal rods disposed in parallel relationship.

10 15. An apparatus as recited in Claim 12, wherein the elongated body portion include means for selectively adjusting the length of the body portion.

15 16. An apparatus as recited in Claim 15, wherein the means for selectively adjusting the length of the body portion includes a first body portion having an axial bore defined therein and a second body portion having an axial shaft for reception within the axial bore of the first body portion, and a locking ring for radially compressing the first body portion against the second body portion when the axial shaft is disposed within the axial bore.

20 17. An apparatus as recited in Claim 15, wherein the means for selectively adjusting the length of the body portion includes a first body portion having a threaded bore defined therein and a second body portion having an threaded shaft for reception within the threaded bore of the first body portion.

18. An apparatus as recited in Claim 12, wherein the cam lug has a generally cylindrical body having camming surfaces formed thereon, and the bore is defined at least in part by interior walls, whereby the camming surfaces of the cam lug are adapted and configured for bearing against the interior walls of the bore upon rotation of the cam lug within the reception bore.

19. An apparatus as recited in Claim 12, wherein the elongated body portion includes opposed first and second end sections, and wherein a clamp portion depends from each end section of the elongated body portion.

10

20. An apparatus for connecting spinal rod comprising:

a) an elongated body portion;

b) a clamp portion depending from the body portion for

engaging a spinal rod, the clamp portion defining a deflectable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body; and

c) an engagement tab projecting from an exterior surface of the clamp body and a recess formed within the clamp body spaced from the engagement tab for effectuating movement of the opposed clamp arms of the clamp body between the first and second positions.

20

21. An apparatus as recited in Claim 20, wherein the elongated body portion includes opposed first and second end sections, and wherein a clamp portion depends from each end section of the elongated body portion.

5 22. An apparatus as recited in Claim 20, wherein the elongated body portion has a predetermined span length for extending between a pair of elongated spinal rods disposed in parallel relationship.

10 23. An apparatus as recited in Claim 20, wherein the elongated body portion has a span length that is selectively variable for extending between a pair of elongated spinal rods disposed in parallel relationship.

24. An apparatus as recited in Claim 23, wherein the elongated body portion include means for selectively adjusting the length of the body portion.

15

25. An apparatus as recited in Claim 24, wherein the means for selectively adjusting the length of the body portion includes a first body portion having an axial bore defined therein and a second body portion having an axial shaft for reception within the axial bore of the first body portion, and a locking ring for radially compressing the first body portion against the second body portion when the axial shaft is disposed within the axial bore.

20

26. An apparatus as recited in Claim 24, wherein the means for selectively adjusting the length of the body portion includes a first body portion having a threaded bore defined therein and a second body portion having an threaded shaft for reception within the threaded bore of the first body portion.

5

27. An apparatus for connecting spinal rod comprising:

a) a first body member having first and second end portions, the first end portion defining a rod clamp for engaging a first spinal rod, the second end portion defining an axial bore, said bore having a radially compressible opening;

10

b) second body member having first and second end portions, the first end portion defining a rod clamp for engaging a second spinal rod, the second end portion defining an axial shaft dimensioned and configured for reception within the axial bore of the first body member;

c) an annular locking collet operatively associated with the second end portion of the first body member, and mounted for movement between a first position wherein the annular collar is spaced from the radially compressible opening of the bore, and a second position wherein the annular collar surrounds and compresses the radially compressible opening of the bore, so as to secure position of the axial shaft of the second body member within the axial bore of the first body member.

15
20

28. An apparatus as recited in Claim 27, wherein the annular locking collet is mounted for movement between an annular blocking flange defined intermediate the second end portion of the first body member and a pair of opposed blocking tabs defined adjacent a distal end of the second end portion of the first body member.

25

29. An apparatus as recited in Claim 27, wherein the rod clamp associated with each of the first and second body members is defined by a deflectable clamp body having opposed clamp arms configured for movement between a first position wherein a spinal rod is received between the opposed clamp arms of the clamp body and a second position wherein the spinal rod is securely engaged by the opposed clamp arms of the clamp body.

30. An apparatus as recited in Claim 29, further comprising means for moving the opposed clamp arms between the first position and second positions.

31. An apparatus as recited in Claim 30, wherein the means for moving the opposed clamp arms between the first position and second positions comprises a cam lug configured for reception within a bore formed in the clamp body and adapted for axial rotation within the bore.

32. An apparatus as recited in Claim 31, wherein the cam lug has a generally cylindrical body having camming surfaces formed thereon, and the reception bore is defined at least in part by interior walls, whereby the camming surfaces of the cam lug are adapted and configured for bearing against the interior walls of the reception bore upon rotation of the cam lug within the reception bore.

33. An apparatus as recited in Claim 30, wherein the means for moving the opposed clamp arms between the first position and the second portion comprises an engagement tab projecting outwardly from an exterior surface of the clamp body, and a recess formed within the clamp body spaced from the engagement tab.

34. A kit for connecting a spinal rods during a spinal stabilization procedure comprising:

- a) a plurality of rod connectors having an elongated body with
5 opposed end portions, a deflectable rod clamp depending from each end portion of the elongated body of each rod connector, each rod clamp having a reception bore defined therein for receiving a rotatable cam lug;
- b) a plurality of rotatable cam lugs; and
- c) an enclosure for housing the plurality of rod connectors and
10 plurality of rotatable cam lugs.

35. A kit as recited in Claim 34, wherein each rod connector has a different span length.

15 36. A kit as recited in Claim 35, wherein the span lengths of the rod connectors range from about 16mm to about 24mm.


37. A kit as recited in Claim 34, further comprising a tool for rotating a cam lug within a reception bore of a rod clamp.


20

38. A kit as recited in Claim 34, wherein a rotatable cam lug is positioned within each reception bore of a rod clamp.

39. A kit as recited in Claim 34, further comprising a plurality of
25 variable length rod connectors.

40. A kit as recited in Claim 39, further comprising a tool for setting a span length of each variable length rod connector in the kit.








FIG. 2











FIG. 3










7/9





9/9



INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/08318

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 813 845 A (EUROS SA) 29 December 1997 (1997-12-29) the whole document	1,2,6-9, 12-15, 19-24, 27,29, 30,34, 35,39,40
A	EP 0 836 836 A (SPINAL INNOVATIONS) 22 April 1998 (1998-04-22) the whole document	1,2, 6-17, 19-27, 29,30, 34,35, 39,40

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

25 July 2000

Date of mailing of the international search report

31/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vereist, P

INTERNATIONAL SEARCH REPORT

Inter nal Application No

PCT/US 00/08318

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 578 320 A (SQUIBB BRISTOL MYERS CO) 12 January 1994 (1994-01-12) cited in the application</p> <p>the whole document -----</p>	<p>1,2, 6-10, 12-17, 19-25, 27,29, 30,34, 35,39,40</p>

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter nal Application No

PCT/US 00/08318

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0813845 A	29-12-1997	FR 2750033 A	26-12-1997
EP 0836836 A	22-04-1998	CA 2217517 A	18-04-1998
		JP 10243948 A	14-09-1998
EP 0578320 A	12-01-1994	US 5312405 A	17-05-1994
		AU 3862093 A	13-01-1994
		CA 2096108 A	07-01-1994
		JP 6165788 A	14-06-1994